

according to 1907/2006/EC, Article 31, as amended by UK REACH Regulations SI 2019/758

Printing date 14.07.2023 Version number 7 (replaces version 6) Revision: 14.07.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product indentifier Ink jet printing ink
- · Range IJC261 UV INK
- · Product Codes

3010117690/3010117710 0040C007AA 3L/0040C001AA 2L IJC261 Black Ink 3010117713/3010117693 0040C010AA 3L/0040C004AA 2L IJC261 Yellow Ink 3010117691/3010117711 0040C008AA 3L/0040C002AA 2L IJC261 Cyan Ink 3010117696/3010117716 0040C011AA 3L/0040C005AA 2L IJC261 Light Cyan Ink 3010117697/3010117717 0040C012AA 3L/0040C006AA 2L IJC261 Light Magenta Ink 3010117692/3010117712 0040C009AA 3L/0040C003AA 2L IJC261 Magenta Ink

1A80-P0C3-Q00P-UXVN black V880-50NQ-E006-6M9K yellow 3280-508W-T006-VX4F cyan JE80-601H-1006-H9FQ light cyan KH80-P0QW-A00P-5N1S light magenta Q580-NOYA-300Q-H8QH magenta

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against The product should not be used for any purpose other than that specified in Section 1.
- · **Product category** PC18 Ink and toners
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer:

Fujifilm Speciality Ink Systems Limited Pysons Road, Broadstairs, Kent. CT10 2LE. Tel. +44 (0)1843 866668

· Distributer:

Canon Production Printing Netherlands B.V. Address: Van der Grintenstraat 10, 5914 HH Venlo, the Netherlands Telephone no.: +31 77 359 2222 e-mail address: sds-hq@cpp.canon

· Information department:

Regulatory Affairs Department Office hours +44(0)1843 866668 (0830 to 1700 GMT) fsis.product-safety @fujifilm.com

· 1.4 Emergency telephone number:

For chemical emergencies only: + 44 (0) 1235 239 670 National Poison Information number: 111

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to regulation (EC) No 1272/2008, as amended for GB-CLP

Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2 H319 Causes serious eye irritation. Skin Sens. 1 H317 May cause an allergic skin reaction. Repr. 2 H361d Suspected of damaging the unborn child. H335 May cause respiratory irritation. STOT SE 3 H372 Causes damage to the liver and the respiratory system STOT RE 1 through prolonged or repeated exposure. Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to regulation (EC) No 1272/2008, as amended for GB-CLP The product is classified and labelled according to the GB CLP regulation.
- · Hazard pictograms







according to 1907/2006/EC, Article 31, as amended by UK REACH Regulations SI 2019/758

Printing date 14.07.2023 Version number 7 (replaces version 6) Revision: 14.07.2023

Range IJC261 UV INK

· Signal word Danger

(Contd. of page 1)

· Hazard-determining components of labelling:

2-Phenoxyethyl Acrylate Isobornyl Acrylate 2H-Azepin-2-one, 1-ethanyhexahydro Trimethylolpropane formalacrylate

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H361d Suspected of damaging the unborn child.

H335 May cause respiratory irritation.

H372 Causes damage to the liver and the respiratory system through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing mist/vapours/spray. P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

- · 2.3 Other hazards
- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Determination of endocrine-disrupting properties Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 48145-04-6 EINECS: 256-360-6 Reg.nr.: 01-2119980532-35	2-Phenoxyethyl Acrylate Repr. 2, H361d Aquatic Chronic 2, H411 Skin Sens. 1A, H317	10-30
CAS: 66492-51-1 EINECS: 266-380-7 Reg.nr.: 01-2119976303-36	Trimethylolpropane formalacrylate Skin Irrit. 2, H315; Skin Sens. 1, H317	10-30
CAS: 2235-00-9 EINECS: 218-787-6 Reg.nr.: 01-2119977109-27	2H-Azepin-2-one, 1-ethanyhexahydro STOT RE 1, H372 Acute Tox. 4, H302; Acute Tox. 4, H312; Eye Irrit. 2, H319; Skin Sens. 1, H317 Specific concentration limit: STOT RE 1;H372: C ≥ 10 %	10-30
CAS: 5888-33-5 EINECS: 227-561-6 Reg.nr.: 01-2119957862-25	Isobornyl Acrylate Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335 Specific concentration limit: STOT SE 3;H335: C ≥ 10 %	10-20
CAS: 56641-05-5 NLP: 500-133-9 Reg.nr.: Not Applicable	Phenol, ethoxylated esters with acrylic acid Aquatic Chronic 2, H411 Skin Sens. 1, H317	1-5%

GB

according to 1907/2006/EC, Article 31, as amended by UK REACH Regulations SI 2019/758

Printing date 14.07.2023 Version number 7 (replaces version 6) Revision: 14.07.2023

Range IJC261 UV INK

	(Contd	. of page 2)
CAS: 75980-60-8 EINECS: 278-355-8 Reg.nr.: 01-2119972295-29	Diphenyl(2,4,6-trimethylbenzoyl) phosphine oxide Repr. 2, H361fd Aquatic Chronic 2, H411 Skin Sens. 1, H317	1-5%
CAS: 162881-26-7 ELINCS: 423-340-5 Reg.nr.: 01-2119489401-38	Phosphine oxide, phenylbis(2,4,6-trimethylbenzoyl)-Skin Sens. 1, H317Aquatic Chronic 4, H413	1-5%
CAS: 15625-89-5 EINECS: 239-701-3 Reg.nr.: 01-2119489896-11	trimethylolpropane triacrylate Carc. 2, H351 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	<1%

· Additional information

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information Immediately remove any clothing soiled by the product.
- · After inhalation Supply fresh air; consult doctor in case of complaints.
- · After skin contact

Immediately wash with soap and water and rinse thoroughly. If skin irritation continues, consult a doctor.

· After eye contact

Rinse open eye for several minutes under running water. Then consult a doctor.

· After swallowing

Give patient copious amounts of water to drink and provide fresh air. Call for a doctor immediately.

- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents Water with full jet.
- 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

Nitrogen oxides (NOx)

Under certain fire conditions, traces of other toxic gases cannot be excluded.

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained breathing apparatus.
- · Additional information

Cool endangered containers with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures





Refer to the protective measures stated in Sections 7 and 8. Keep unprotected personnel away.

(Contd. on page 4)

according to 1907/2006/EC, Article 31, as amended by UK REACH Regulations SI 2019/758

Printing date 14.07.2023 Version number 7 (replaces version 6) Revision: 14.07.2023

Range IJC261 UV INK

(Contd. of page 3)

Ensure adequate ventilation

- · For non-emergency personnel Remove personnel from danger area.
- · For emergency responders Wear protective clothing.
- · 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course. Inform respective authorities if seepage into water course or sewage system

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomaceous earth, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to section 13.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Store in cool, dry place in tightly sealed containers.

Keep away from heat and direct sunlight.

Ensure good ventilation and extraction at the workplace.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage: Store in accordance with current national regulations.
- Requirements to be met by storerooms and containers: Store between 5 30°C.
- · Information about storage in one common storage facility:

Do not store together with oxidising and acidic materials.

Do not store together with alkalis (caustic solutions).

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Components with limit values that require monitoring at the workplace:
- · DNELs

worker:

8145-04-6	2-Phen	oxyethyl Acrylate
Dermal	DNEL	
Inhalation		
2235-00-9 2	H-Azep	in-2-one, 1-ethanyhexahydro
Dermal	DNEL	0.7 mg/kg (-) (long term exposure systemic effects)
Inhalation	DNEL	4.9 mg/m3 (-) (Long-term exposure-systemic effects) 0,17 mg/m3 (-) (Long Term exposure-local effects)
5888-33-5 I	soborn	yl Acrylate
Dermal	DNEL	1.39 mg/kg (-) (Long-Term exposure, Systemic effects)
Inhalation	DNEL	1.64 mg/m3 (-) (Long Term exposure, Systemic effects)
162881-26-7	Phosp	hine oxide, phenylbis(2,4,6-trimethylbenzoyl)-
Dermal	DNEL	3.3 mg/kg (-) (Long Term)
Inhalation	DNEL	7.8 mg/m3 (-) (Long Term)
15625-89-5	trimet	hylolpropane triacrylate
Dermal	DNEL	83 mg/kg (-) (Long Term)
Inhalation	DNEL	3.5 mg/m3 (-) (Long Term)
PNECs		
2235-00-9 2	H-Azep	in-2-one, 1-ethanyhexahydro
0,01 0,829	mg/1 (mg/kg	e) (Fresh Water) (-) (Marine Water) ((-) (Sediment Freshwater) (g (-) Sediment Marine water)

(Contd. on page 5)

according to 1907/2006/EC, Article 31, as amended by UK REACH Regulations SI 2019/758

Printing date 14.07.2023 Version number 7 (replaces version 6) Revision: 14.07.2023

Range IJC261 UV INK

(Contd. of page 4)

· Additional information:

The instructions and information provided by the manufacturer of the personal protective equipment on use, storage, maintenance and replacement must always be followed.

· 8.2 Exposure controls

· General protective and hygienic measures

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. Store protective clothing separately.

· Breathing equipment:

Provide a good standard of general ventilation (not less than 3-5 air changes per hour)

In cases of insufficient ventilation use the following respiratory protective device:

Filter A/P2.

· Hand protection

Use of the following recommended:

Туре			Heavy Duty	Single	e Multi	Neoprene Heavy Duty (Gauntlets)
Preparation Print Shop	X	Y	X	X	Y	X
Solvent Inks	Y	Y	Y	Y	Y	Y
UV Inks	X	X	X	Y	Y	Y
Reclaim	X	X	Y	X	X	Y

Y = recommended X = not recommended

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. The selection of single or multi-use gloves is dependent upon the level of exposure.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance. Always ensure that gloves are free from defects and that they are stored and used correctly.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

 ${\it Hands}$ should be inspected on a regular basis for any signs of skin damage or inflammation

Single use disposable nitrile gloves (short duration exposure of few minutes, or where only splashes likely). Not to be reused when removed.

Minimum 0.4mm thick neoprene or nitrile gloves (longer duration exposure or mechanical handling activities). To be replaced immediately when punctured or degraded.

Heavy duty unlined neoprene gloves (when using solvents). To be replaced immediately when punctured or degraded.

· Penetration time of glove material

The exact break through time has to be obtained from the manufacturer of the protective gloves and must be observed.

- · Eye/face protection Safety glasses
- · Body protection:

Protective work clothing; disposable overalls are preferable.

Acrylates, like any other organic solvent, are skin and/or eye irritants. Since acrylates do not evaporate, they will remain on the skin or clothes for extended periods. This long term exposure, caused by the non volatility, can give rise to dermatitis. It is essential that the measures given above are always followed.

· COSHH Essentials for Printers Control Guidance Sheet:

Guidance is provided by the Health and Safety executive (HSE) concerning COSHH (Control of Substances Hazardous to Health) for printers. See COSHH Essentials for Printers on the HSE website:

www.hse.gov.uk and enter 'COSHH Essentials for printers' in the search bar.

according to 1907/2006/EC, Article 31, as amended by UK REACH Regulations SI 2019/758

Printing date 14.07.2023 Version number 7 (replaces version 6) Revision: 14.07.2023

Range IJC261 UV INK

(Contd. of page 5)

SECTION 9: Physical and chemical properties			
· 9.1 Information on basic physical and	chemical properties		
· General Information			
· Colour:	According to product specification		
· Odour:	Characteristic		
· Odour threshold:	Not determined.		
· Melting point/freezing point:	undetermined		
· Boiling point or initial boiling point			
and boiling range	undetermined		
Flammability	Not determined.		
· Lower and upper explosion limit			
· Lower:	Not determined.		
· Upper:	Not determined.		
· Flash point:	Not applicable		
· Auto-ignition temperature:	Not applicable		
· Decomposition temperature:	Not determined.		
· pH	Not determined.		
· Viscosity:	Not determined		
· Kinematic viscosity	Not determined.		
-			
dynamic:	Not determined.		
· Water:	Not miscible or difficult to mix		
· Partition coefficient n-octanol/water			
(log value)	Not determined.		
· Vapour pressure:	Not determined.		
 Density and/or relative density 			
· Density at 20 °C:	1.08 g/cm³		
· Relative density	Not determined.		
· Vapour density	Not determined.		
· 9.2 Other information			
· Appearance:			
· Form:	Liquid		
· Important information on protection of			
health, safety and the environment.			
· Self igniting:	Product is not selfigniting.		
· Explosive properties:	Product does not present an explosion		
	hazard.		
· Solvent content:			
· Organic solvents:	0.0 %		
· Change in condition			
· Softening point/range			
	NT - t - d - t - com t d		
· Oxidising properties	Not determined		
· Evaporation rate	Not determined.		
· Information with regard to physical			
hazard classes			
· Explosives	Void		
· Flammable gases	Void		
· Aerosols	Void		
Oxidising gases	Void		
Gases under pressure	Void		
\cdot Flammable liquids	Void		
· Flammable solids	Void		
· Self-reactive substances and mixtures	Void		
· Pyrophoric liquids	Void		
· Pyrophoric solids	Void		
· Self-heating substances and mixtures	Void		
· Substances and mixtures, which emit			
flammable gases in contact with water	Void		
· Oxidising liquids	Void		
Oxidising solids	Void		
· Organic peroxides	Void		
· Corrosive to metals	Void		
	(Contd. on page 7)		

according to 1907/2006/EC, Article 31, as amended by UK REACH Regulations SI 2019/758

Printing date 14.07.2023 Version number 7 (replaces version 6) Revision: 14.07.2023

Range IJC261 UV INK

(Contd. of page 6)

• Desensitised explosives

Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Stable until: 50°C
- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

48145-04-6	2-Phenoxy	ethyl Acrylate
Dermal	LD50	>2,000 mg/kg (rat)
2235-00-9 2	H-Azepin-	2-one, 1-ethanyhexahydro
Oral	LD50	1,860 mg/kg (rat) ((OECD Guideline 401))
Dermal	LD50	>2,000 mg/kg (rat)
		1,700 mg/kg (rabbit) (OECD Guideline 402)
Inhalation	LC50 8h	>1.6 mg/l (rat)
5888-33-5 1	sobornyl	Acrylate
Oral	LD50	4,350 mg/kg (rat)
162881-26-7	Phosphin	e oxide, phenylbis(2,4,6-trimethylbenzoyl)-
Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
15625-89-5	trimethyl	olpropane triacrylate
Oral	LD50	3,680 mg/kg (rat)
	LD50	5,170 mg/kg (rabbit)

· Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

· Germ cell mutagenicity

Based on available data, the classification criteria are not met.

- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity

Suspected of damaging the unborn child.

· STOT-single exposure

May cause respiratory irritation.

· STOT-repeated exposure

Causes damage to the liver and the respiratory system through prolonged or repeated exposure.

· Aspiration hazard

Based on available data, the classification criteria are not met.

· 11.2 Information on other hazards Void

- GE

according to 1907/2006/EC, Article 31, as amended by UK REACH Regulations SI 2019/758

Printing date 14.07.2023 Version number 7 (replaces version 6) Revision: 14.07.2023

Range IJC261 UV INK

(Contd. of page 7)

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic to	Aquatic toxicity:						
66492-51-1	66492-51-1 Trimethylolpropane formalacrylate						
LC50/96 h	4 mg/l (Oncorhynchus mykiss)						
5888-33-5	Isobornyl Acrylate						
LC50/96 h	0.7 mg/l (Zebra fish) (OECD Test Guideline 203)						
EC50/72 h	1.98 mg/l (algae) (OECD Test Guideline 201, Growth inhibition)						
162881-26-	7 Phosphine oxide, phenylbis(2,4,6-trimethylbenzoyl)-						
LC50/96 h	>0.09 mg/l (Brachydanio rerio)						
EC50/48 h	>1.175 mg/l (Daphnia)						
EC50/72 h	0.26 mg/l (algae)						
IC50	>100 mg/l (Sewage sludge)						
15625-89-5	15625-89-5 trimethylolpropane triacrylate						
LC50/96 h	1-10 mg/l (Daphnia)						
EC50/48 h	10-100 mg/l (Daphnia)						
EC50/72 h	1-10 mg/l (algae)						

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects No further relevant information available.
- · Additional ecological information:
- · General notes:

There are no data on the preparation itself.

The preparation has been assessed following the conventional method of the GB CLP Directive 1272/2008/EC, as amended for Great Britain and is classified as dangerous for the environment. Also refer to Sections 2 and 15.



Do not allow product to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation



Must not be disposed together with household rubbish. Do not allow product to reach sewage system.

· European waste catalogue

08 03 12* | waste ink containing hazardous substances

Waste Hazard Classification:

HP 5 - Specific target Organ Toxicity/Aspiration Toxicity

HP 10 - Toxic for reproduction

HP 4 - Irritant

HP 13 - Sensitising

HP 14 - Eco Toxic

· Recommendation:

Dispose of product according to official regulations.

(Contd. on page 9)

according to 1907/2006/EC, Article 31, as amended by UK REACH Regulations SI 2019/758

Printing date 14.07.2023 Version number 7 (replaces version 6) Revision: 14.07.2023

Range IJC261 UV INK

Also see Section 16 'Other Information'

(Contd. of page 8)

SECTION 14: Transport informa	tion
· 14.1 UN number or ID number · ADR, IMDG, IATA	UN3082
· 14.2 UN proper shipping name · ADR	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Acrylate Monomer)
· IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Acrylate Monomer), MARINE POLLUTANT
· IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Acrylate Monomer)
· 14.3 Transport hazard class(es) · ADR, IMDG, IATA	
1 1 1 1 1 1 1 1 1 1	
· Class	9 Miscellaneous dangerous substances and articles. 9
· 14.4 Packing group · ADR, IMDG, IATA	III
· 14.5 Environmental hazards: · Marine pollutant:	Yes Symbol (fish and tree)
· Special marking (ADR): · Special marking (IATA):	Symbol (fish and tree) Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Miscellaneous dangerous substances and articles.
 Hazard identification number (Kemle code): EMS Number: 	90 F-A,S-F
· Stowage Category	A A
 14.7 Maritime transport in bulk according to IMO instruments 	Not applicable.
· Transport/Additional information:	Single or combination packagings containing a net quantity per single or inner packaging of 51t/5kg or less of UN3082, are not subject to the provisions of ADR (Special Provision 375), IMDG (2.10.2.7) or IATA (special provision 197) by way of a pack size exemption.
· ADR	
· Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category · Tunnel restriction code	3 E
· IMDG	
· Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml
<u> </u>	(Contd. on page 10)

according to 1907/2006/EC, Article 31, as amended by UK REACH Regulations SI 2019/758

Printing date 14.07.2023 Version number 7 (replaces version 6) Revision: 14.07.2023

Range IJC261 UV INK

	(Contd. of page 9)
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ACRYLATE MONOMER), 9, III

SECTION 15: Regulatory information

- · 15.2 Chemical Safety Assessment Chemical Safety Assessment not applicable
- · 15.28 Safety, health and environmental regulations/legislation specific for the substance or mixture

No further relevant information available.

- · Directive 2012/18/EU, Seveso III Directive, as amended for Great Britain
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- \cdot Seveso category E2 Hazardous to the Aquatic Environment
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII, as amended for Great Britain Conditions of restriction: 3
- · DIRECTIVE 2011/65/EU, as amended for Great Britain, on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II None of the ingredients is listed.
 - · REGULATION (EU) 2019/1148, as amended for Great Britain
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

- · Regulation (EC) No 273/2004 on drug precursors, as amended for Great Britain None of the ingredients is listed.
- Regulation (EC) No 111/2005, as amended for Great Britain, laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

- · National regulations
- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57

75980-60-8 Diphenyl(2,4,6-trimethylbenzoyl) phosphine oxide

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The safety data sheets is in compliance with regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878

An "*" in the left hand margin indicates an amendment from the previous version.

· Relevant phrases

- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H361d Suspected of damaging the unborn child.

(Contd. on page 11)

according to 1907/2006/EC, Article 31, as amended by UK REACH Regulations SI 2019/758

Printing date 14.07.2023 Version number 7 (replaces version 6) Revision: 14.07.2023

Range IJC261 UV INK

```
(Contd. of page 10)
   H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
                    Causes damage to organs through prolonged or repeated exposure.
   H400
                    Very toxic to aquatic life.
   H410
                    Very toxic to aquatic life with long lasting effects.
                    Toxic to aquatic life with long lasting effects.
   H411
                   May cause long lasting harmful effects to aquatic life.
· Recommended restriction of use
   The product should not be used for any purpose other than that specified in
   Section 1.
· Department issuing SDS:
   Regulatory Affairs Department - Fujifilm Speciality Ink Systems Limited
· Contact: fsis.product-safety@fujifilm.com
· Version number of previous version: 6
· Abbreviations and acronyms:
   ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
    IMDG: International Maritime Code for Dangerous Goods
   IATA: International Air Transport Association (IATA Dangerous Goods Regulation (DGR) 64th Edition 2023) GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances
   ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
    DNEL: Derived No-Effect Level (UK REACH)
    PNEC: Predicted No-Effect Concentration (UK REACH)
   LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
SVHC: Substances of Very High Concern
vPvB: very Persistent and very Bioaccumulative
Acute Tox. 4: Acute toxicity - Category 4
Skin Irrit. 2: Skin corrosion/irritation - Category 2
Eve Irrit 2: Serious eve damage/eve irritation - Category 2
  Skin Irrit. 2: Skin corrosion/irritation - Category 2
Eye Irrit. 2: Serious eye damage/eye irritation - Category 2
Skin Sens. 1: Skin sensitisation - Category 1
Skin Sens. 1A: Skin sensitisation - Category 1A
Carc. 2: Carcinogenicity - Category 2
Repr. 2: Reproductive toxicity - Category 2
Repr. 2: Reproductive toxicity - Category 2
STOT SE 3: Specific target organ toxicity (single exposure) - Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2
Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4
```