

Hoja de datos de seguridad

según NOM 018-STPS-2015

Printing date 08.08.2023 Version number 7 Revision: 08.08.2023

SECTION 1: Identificación de la sustancia química peligrosa o mezcla y del proveedor o fabricante

- \cdot 1.1 Product indentifier Ink jet printing ink
- · Range IJC261 UV INK
- · Product Codes

3010117690/3010117710 0040C007AA 3L/0040C001AA 2L IJC261 Black Ink
3010117713/3010117693 0040C010AA 3L/0040C004AA 2L IJC261 Yellow Ink
3010117691/3010117711 0040C008AA 3L/0040C002AA 2L IJC261 Cyan Ink
3010117696/3010117716 0040C011AA 3L/0040C005AA 2L IJC261 Light Cyan Ink
3010117697/3010117717 0040C012AA 3L/0040C006AA 2L IJC261 Light Magenta Ink
3010117692/3010117712 0040C009AA 3L/0040C003AA 2L IJC261 Magenta Ink

- 1.2 Relevant identified uses of the substance or mixture and uses advised against
 The product should not be used for any purpose other than that specified in
 Section 1.
- · Product category PC18 Ink and toners
- · Manufacturer:

Fujifilm Speciality Ink Systems Limited
Pysons Road, Broadstairs, Kent. CT10 2LE.
Tel. +44 (0)1843 866668
Canon Mexicana, S. De R.L. De C.V.
Boulevard Manuel Ávila Camacho No. 138,
Col. Lomas de Chapultepec, C.P. 11000, México, D.F
Phone:+52 55 5249 4900

- · Information department: Product Safety Department
- · 1.4 Emergency telephone number:

For chemical emergencies only: + 52 555 004 8763 CHEMTREC 1-703-741-5500

SECTION 2: Identificación de los peligros

- · 2.1 Classification of the substance or mixture
- · Classification according to regulation (EC) No 1272/2008, as amended for GB-CLP

Skin Irrit. 2

H315 Causes skin irritation.

Serious eye damage/irritation - Category 2A

Skin Sens. 1

H317 May cause an allergic skin reaction.

Repr. 2

H361 Suspected of damaging fertility or the unborn child.

STOT SE 3

H375 Causes skin irritation.

H376 Causes damage to the liver and the respiratory system through prolonged or repeated exposure.

- · 2.2 Label elements
- Labelling according to regulation (EC) No 1272/2008, as amended for GB-CLP The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms





GHS07 GHS0

- · Signal word Danger
- · Hazard-determining components of labelling:

2-Phenoxyethyl Acrylate 2H-Azepin-2-one, 1-ethanyhexahydro Trimethylolpropane formalacrylate Isobornyl Acrylate

Hazard statements

H315 Causes skin irritation. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction.

(Contd. on page 2)

Printing date 08.08.2023

Version number 7

Range IJC261 UV INK

(Contd. of page 1)

Revision: 08.08.2023

H361 Suspected of damaging fertility or the unborn child.

H335 May cause respiratory irritation.

H372 Causes damage to the liver and the respiratory system through prolonged or repeated exposure.

· Precautionary statements

P261 Avoid breathing mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Determination of endocrine-disrupting properties Not applicable.

SECTION 3: Composición / información sobre los componentes

- · 3.2 Chemical characterisation: Mixture
- · Description: Mixture of substances listed below with nonhazardous additions.

CAS: 48145-04-6	2-Phenoxyethyl Acrylate	10-30%
EINECS: 256-360-6	Repr. 2, H361 Skin Sens. 1, H317 Acute Tox. 5, H313	
CAS: 66492-51-1 EINECS: 266-380-7	Trimethylolpropane formalacrylate Skin Irrit. 2, H315; Skin Sens. 1, H317	10-30
CAS: 2235-00-9 EINECS: 218-787-6	2H-Azepin-2-one, 1-ethanyhexahydro STOT RE 1, H372 Acute Tox. 4, H302; Acute Tox. 4, H312; Serious eye damage/irritation - Category 2A, H319; Skin Sens. 1, H317	10-30 %
CAS: 5888-33-5 EINECS: 227-561-6	Isobornyl Acrylate Skin Irrit. 2, H315; Serious eye damage/irritation - Category 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335 Acute Tox. 5, H303	10-20
CAS: 56641-05-5 NLP: 500-133-9	Phenol, ethoxylated esters with acrylic acid Skin Sens. 1, H317	1-5%
CAS: 75980-60-8 EINECS: 278-355-8	Diphenyl(2,4,6-trimethylbenzoyl) phosphine oxide Repr. 2, H361 Skin Sens. 1, H317	1-5%
CAS: 162881-26-7 ELINCS: 423-340-5	Phosphine oxide, phenylbis(2,4,6-trimethylbenzoyl)- Skin Sens. 1, H317 Acute Tox. 5, H303; Acute Tox. 5, H313	1-5%
CAS: 15625-89-5 EINECS: 239-701-3	trimethylolpropane triacrylate Carc. 2, H351 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 Acute Tox. 5, H303	<1%

· SVHC

75980-60-8 Diphenyl(2,4,6-trimethylbenzoyl) phosphine oxide

Additional information

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: Primeros auxilios

- · 4.1 Description of first aid measures
- · General information Immediately remove any clothing soiled by the product.
- · After inhalation Supply fresh air; consult doctor in case of complaints.

(Contd. on page 3)

Printing date 08.08.2023

Version number 7

Range IJC261 UV INK

(Contd. of page 2)

Revision: 08.08.2023

· After skin contact

Immediately wash with soap and water and rinse thoroughly. If skin irritation continues, consult a doctor.

· After eye contact

Rinse open eye for several minutes under running water. Then consult a doctor.

· After swallowing

Give patient copious amounts of water to drink and provide fresh air. Call for a doctor immediately.

· 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Medidas contra incendios

- · 5.1 Extinguishing media
- · Suitable extinguishing agents

 ${\it CO2}$, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents Water with full jet.
- · 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

Nitrogen oxides (NOx)

Under certain fire conditions, traces of other toxic gases cannot be excluded.

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained breathing apparatus.
- · Additional information

Cool endangered containers with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Medidas que deben tomarse en caso de derrame o fuga accidental

· 6.1 Personal precautions, protective equipment and emergency procedures





Refer to the protective measures stated in Sections 7 and 8. Keep unprotected personnel away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course. Inform respective authorities if seepage into water course or sewage system occurs.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomaceous earth, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to section 13.

 \cdot 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Manejo y almacenamiento

· 7.1 Precautions for safe handling

Store in cool, dry place in tightly sealed containers. Keep away from heat and direct sunlight.

Ensure good ventilation and extraction at the workplace.

- · 7.2 Conditions for safe storage, including any incompatibilities
- \cdot ${\it Storage:}$ Store in accordance with current national regulations.
- · Requirements to be met by storerooms and containers: Store between 5 30°C.

(Contd. on page 4)

Printing date 08.08.2023

Version number 7

Range IJC261 UV INK

(Contd. of page 3)

Revision: 08.08.2023

· Information about storage in one common storage facility:

Do not store together with oxidising and acidic materials. Do not store together with alkalis (caustic solutions).

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Controles de exposición / protección personal

· 8.1 Control parameters

· Components	with limit values that require monitoring at the workplace:
15625-89-5	trimethylolpropane triacrylate
WEEL (USA)	VLE-PPT: 1 mg/m³
	Skin

· DNELs

worker:

48145-04-6	2-Phen	oxyethyl Acrylate
Dermal	DNEL	3.5 mg/kg (-) (Long Term)
Inhalation	DNEL	12 mg/m3 (-) (Long Term)
2235-00-9 2	H-Azep	in-2-one, 1-ethanyhexahydro
Dermal	DNEL	0.7 mg/kg (-) (long term exposure systemic effects)
Inhalation	DNEL	4.9 mg/m3 (-) (Long-term exposure-systemic effects)
5888-33-5 I	soborn	yl Acrylate
Dermal	DNEL	1.39 mg/kg (-) (Long-Term exposure, Systemic effects)
Inhalation	DNEL	1.64 mg/m3 (-) (Long Term exposure, Systemic effects)
162881-26-7	Phosp	hine oxide, phenylbis(2,4,6-trimethylbenzoyl)-
Dermal	DNEL	3.3 mg/kg (-) (Long Term)
Inhalation	DNEL	7.8 mg/m3 (-) (Long Term)
15625-89-5	trimet	hylolpropane triacrylate
Dermal	DNEL	83 mg/kg (-) (Long Term)
Inhalation	DNEL	3.5 mg/m3 (-) (Long Term)

· PNECs

2235-00-9 2H-Azepin-2-one, 1-ethanyhexahydro

PNEC | 0.1 mg/l (-) (Fresh Water)

Additional information:

The instructions and information provided by the manufacturer of the personal protective equipment on use, storage, maintenance and replacement must always be followed.

· 8.2 Exposure controls

· General protective and hygienic measures

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
Store protective clothing separately.

· Breathing equipment:

Provide a good standard of general ventilation (not less than $3\,$ - $5\,$ air changes per hour)

In cases of insufficient ventilation use the following respiratory protective device:

Filter A/P2.

· Protection of hands:

Туре			Heavy Duty	Single	e Multi	Neoprene Heavy Duty (Gauntlets)	_
Preparation Print Shop	X	Y	X	X	Y	X	
Solvent Inks	Y	Y	Y	Y	Y	Y	
UV Inks	X	X	X	Y	Y	Y	
Reclaim	X	X	Y	X	X	Y	

Y = recommended X = not recommended

(Contd. on page 5)

Printing date 08.08.2023 Version number 7 Revision: 08.08.2023

Range IJC261 UV INK

(Contd. of page 4)

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. The selection of single or multi-use gloves is dependent upon the level of exposure.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance. Always ensure that gloves are free from defects and that they are stored and used correctly.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

 ${\it Hands\ should\ be\ inspected\ on\ a\ regular\ basis\ for\ any\ signs\ of\ skin\ damage\ or\ inflammation}$

Single use disposable nitrile gloves (short duration exposure of few minutes, or where only splashes likely). Not to be reused when removed.

Minimum 0.4mm thick neoprene or nitrile gloves (longer duration exposure or mechanical handling activities). To be replaced immediately when punctured or degraded.

Heavy duty unlined neoprene gloves (when using solvents). To be replaced immediately when punctured or degraded.

· Penetration time of glove material

The exact break through time has to be obtained from the manufacturer of the protective gloves and must be observed.

- · Eye protection: Safety glasses
- · Body protection:

Protective work clothing; disposable overalls are preferable.

Acrylates, like any other organic solvent, are skin and/or eye irritants. Since acrylates do not evaporate, they will remain on the skin or clothes for extended periods. This long term exposure, caused by the non volatility, can give rise to dermatitis. It is essential that the measures given above are always followed.

SECTION 9: Propiedades físicas	y químicas
 9.1 Information on basic physical and General Information Appearance: 	chemical properties
Form: Colour: Odour:	Liquid According to product specification Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
 Change in condition Melting point/freezing point: Initial boiling point and boiling 	undetermined
range:	undetermined
· Flash point:	Not applicable
· Flammability (solid, gaseous)	Not determined.
· Auto-ignition temperature:	Not applicable
· Decomposition temperature:	Not determined.
· Self igniting:	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard.
· Explosion limits: Lower: Upper: · Oxidising properties	Not determined. Not determined. Not determined
· Vapour pressure:	Not determined.
· Density at 20 °C: · Relative density · Vapour density	1.08 g/cm³ Not determined. Not determined.

(Contd. on page 6)

Revision: 08.08.2023

Hoja de datos de seguridad según NOM 018-STPS-2015

Printing date 08.08.2023

Version number 7

Range IJC261 UV INK

	(Contd. of page 5
· Evaporation rate · Water:	Not determined. Not miscible or difficult to mix
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: · dynamic: · kinematic:	Not determined Not determined. Not determined.
· Solvent content: Organic solvents:	0.0 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Estabilidad y reactividad

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: Información toxicológica

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

48145-04-6 2-Phenoxyethyl Acrylate			
Dermal	LD50	>2,000 mg/kg (rat)	
2235-00-9 2H-Azepin-2-one, 1-ethanyhexahydro			
Oral	LD50	1,860 mg/kg (rat) ((OECD Guideline 401))	
Dermal	LD50	>2,000 mg/kg (rat)	
		1,700 mg/kg (rabbit) (OECD Guideline 402)	
Inhalation	LC50 8h	>1.6 mg/l (rat)	
5888-33-5 1	sobornyl	Acrylate	
Oral	LD50	4,350 mg/kg (rat)	
162881-26-7	Phosphin	ne oxide, phenylbis(2,4,6-trimethylbenzoyl)-	
Oral	LD50	>2,000 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rat)	
15625-89-5 trimethylolpropane triacrylate			
Oral	LD50	3,680 mg/kg (rat)	

- · Specific symptoms in biological assay:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity

Based on available data, the classification criteria are not met.

- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity

Suspected of damaging fertility or the unborn child.

· STOT-single exposure

May cause respiratory irritation.

(Contd. on page 7)

Printing date 08.08.2023 Version

Version number 7 Revision: 08.08.2023

Range IJC261 UV INK

· STOT-repeated exposure

(Contd. of page 6)

Causes damage to the liver and the respiratory system through prolonged or repeated exposure.

· Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Información ecotoxicológica

· 12.1 Toxicity

· Aquatic to	xicity:					
66492-51-1	Trimethylolpropane formalacrylate					
LC50/96 h	LC50/96 h 4 mg/l (Oncorhynchus mykiss)					
5888-33-5	Isobornyl Acrylate					
LC50/96 h	0.7 mg/l (Zebra fish) (OECD Test Guideline 203)					
EC50/72 h	1.98 mg/l (algae) (OECD Test Guideline 201, Growth inhibition)					
162881-26-	7 Phosphine oxide, phenylbis(2,4,6-trimethylbenzoyl)-					
LC50/96 h	>0.09 mg/l (Brachydanio rerio)					
EC50/48 h	>1.175 mg/l (Daphnia)					
EC50/72 h	0.26 mg/l (algae)					
IC50	>100 mg/l (Sewage sludge)					
15625-89-5	trimethylolpropane triacrylate					
LC50/96 h	1-10 mg/l (Daphnia)					
EC50/48 h	10-100 mg/l (Daphnia)					
EC50/72 h	1-10 mg/l (algae)					

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

There are no data on the preparation itself.

The preparation has been assessed following the conventional method of the CLP Directive 1272/2008/EC, as amended for Great Britain and is classified as dangerous for the environment. Also refer to Sections 2 and 15.



Do not allow product to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

<u>SECTION</u> 13: Información relativa a la eliminación de los productos

- · 13.1 Waste treatment methods
- · Recommendation



Must not be disposed together with household rubbish. Do not allow product to reach sewage system.

· European waste catalogue

08 03 12* | waste ink containing hazardous substances

Recommendation:

Dispose of product according to official regulations. Also see Section 16 'Other Information'

Printing date 08.08.2023 Version number 7 Revision: 08.08.2023

Range IJC261 UV INK

(Contd. of page 7)

SECTION 14: Información relati	iva al transporte
	_
14.1 UN-Number	*****
ADR, IMDG, IATA	UN3082
14.2 UN proper shipping name	
ADR	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE,
	LIQUID, N.O.S. (Acrylate Monomer)
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE,
	LIQUID, N.O.S. (Acrylate Monomer), MARINE POLLUTANT
IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE,
±11111	LIQUID, N.O.S. (Acrylate Monomer)
14.3 Transport hazard class(es)	2. , , . , , . , . , . , . , .
-	
ADR, IMDG, IATA	
\wedge	
(III) (¥,,)	
, , ,	
*	
Class	9 Miscellaneous dangerous substances and
Taba 7	articles.
Label	9
14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	Yes
	Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
Special marking (IATA):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Miscellaneous dangerous substance
1 / 1 / 1 / 1 / 1 / 1 / 1 / 1 / 1 / 1	and articles.
<pre>Hazard identification number (Kemler code):</pre>	
EMS Number:	90 F-A,S-F
Stowage Category	A A
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
Transport/Additional information:	Single or combination packagings containing
	a net quantity per single or inner
	packaging of 51t/5kg or less of UN3082, as not subject to the provisions of ADR
	(Special Provision 375), IMDG (2.10.2.7)
	IATA (special provision 197) by way of a
	pack size exemption.
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging:
	30 ml
	Maximum net quantity per outer packaging:
Thomasont asterior	1000 ml
Transport category Tunnel restriction gode	3
Tunnel restriction code	_E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging:
	30 ml Maximum net quantity per outer packaging:
	maximum het qualitity per outer packagillg:
	1000 ml

Printing date 08.08.2023 Version number 7 Revision: 08.08.2023

Range IJC261 UV INK

(Contd. of page 8)

· UN "Model Regulation":

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ACRYLATE MONOMER), 9, III

SECTION 15: Información reglamentaria

- 15.2 Chemical Safety Assessment Chemical Safety Assessment not applicable
- 15.28 Safety, health and environmental regulations/legislation specific for the substance or mixture

No further relevant information available.

- · Directive 2012/18/EU, Seveso III Directive, as amended for Great Britain
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category E2 Hazardous to the Aquatic Environment
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

SECTION 16: Otra información

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The safety data sheets is in compliance with regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878

An "*" in the left hand margin indicates an amendment from the previous version.

· Relevant phrases

H302 Harmful if swallowed.

H303 May be harmful if swallowed.

H312 Harmful in contact with skin.

H313 May be harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

· Recommended restriction of use

The product should not be used for any purpose other than that specified in Section 1.

· Department issuing SDS:

Regulatory Affairs Department - Fujifilm Speciality Ink Systems Limited

· Contact: fsis.product-safety@fujifilm.com

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association (IATA Dangerous Goods Regulation (DGR) 64th Edition 2023)

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

MX