PRODUCT SAFETY DATA SHEET

Canon Production Printing Netherlands B.V.

Van der Grintenstraat 10

P.O. Box 101

telephone +31 77 359 2222

Number: EN-HYB370-380e-HQ Date: May 2023

Canon

5914 HH Venlo The Netherlands

For safety questions contact the Product Safety Coordinator of your local sales and service organisation

Product Name(s)	Arizona 1340 GTF, Arizona 1360 GTF, Arizona 1380 GTF, Arizona 1340 XTF, Arizona 1360 XTF, Arizona 1380 XTF all with option RMO		
Model(s)	HYB370 and HYB380		
Description	Flatbed digital color print system		
Process speed	Arizona 13x0 GTF up to 50,9 m²/h and Arizona 13x0 XTF up to 52,8 m²/h Option RMO - Roll Media Printing Up to 38,6 m²/h		
Dimensions:	Arizona 13x0 GTF	Arizona 13x0 XTF	
* width	4656 mm	4656 mm	
* depth	2000 mm (2285 mm with RMO)	3830 mm (4120 mm with RMO)	
* height	Table 888 mm and Gantry 1300 mm	Table 888 mm and Gantry 1300 mm	
* weight	806 kg, with RMO 896 kg	1681 kg, with RMO 1818 kg	
Electrical data:	Arizona 13x0 GTF	Arizona 13x0 XTF	
* voltage	200 - 240 V 50/60Hz		
* current-rated	14 A Inlet 1 and 3 A Inlet 2	16 A Inlet 1 and 16 A Inlet 2	
* building fuse	20 A USA and 16 A EU		
Mains connection	Cable with plug		
Safety class	I (IEC 61140) Protective earth connection		
Protection class	IP2X (IEC 60529)		
EMC Class	Class A (according to EN61000-6-4)		
Safety certification	According to 2006/42/EC BG-listed (DP 18067), UL73 and CSA 22.2 No. 68		
Battery Type (weight)	BR2032 (3,3 g, present on CPU)		
Energy consumption:	Arizona 13x0 GTF	Arizona 13x0 XTF	
* off	0 W	0 W	
* ready	360 W	360 W	
* maximum	2000 W Inlet 1 and 500 W Inlet 2	2400 W Inlet 1 and 2000 W Inlet 2	
Noise emission ¹ :			
* Sound pressure level	L _{pA} less than 71,3 dB (A)	L _{pA} less than 71,3 dB (A)	
(at operator position)			
Heat emission	Not applicable		
Radio interference	Complies with Directive 2014/30/EU and FCC rules and regulations, part 15 Class A.		
Radiation	Not applicable Conservation (and (and (and (and (and (and (and (an		
Chemical emission:	Emission (mg/h) Concentration (mg/m³) ¹		
* dust	8,6 < 0,01		
* ozone	0,0 0,0		
* TVOC	340 0,28		
Recommended room ventilation	≥ 1200 m³ per hour. For heat evacuation extra ventilation may be necessary.		
Consumables	This apparatus is suitable for IJC357 and IJC358 Ink Materials		
Additional safety information	UV inks can be harmful if not properly handled. Follow the guidelines in the User Guide carefully in order to ensure maximum safety.		

1 average concentration, additional to background, calculated for a daily volume of continuous prints during a work time of 8 h at recommended minimal room volume and room ventilation Under normal conditions of use concentrations are considered to remain around or below above concentrations. Concentrations are a best estimate and have been calculated from concentration measurements performed under practical conditions in a room with a volume of 195 m³ and a ventilation rate of 6/h.

Compliance

Approval according to Approval according to Machinery Directive standard UL73 and 2006/42/EC

Approved according UKCA-Compliance 2014/30/EU









This safety data sheet has been compiled to the best of our knowledge as a compact guide to safe handling of this product. We reserve the right to revise safety data sheets as new information becomes available. It is the user's responsibility to determine the suitability of this information for the adoption of safety precautions as may be necessary and to contact the company to make sure that this sheet is the latest one issued. If and in so far as limitation of liability is permitted under the applicable laws, we do not accept liability for any inaccuracy that may occur in this information.